



RUST BULLET® RAPID FIRE™ APPLICATION GUIDELINES

A 100% Solids Accelerator Additive for all Rust Bullet Moisture-Cured Urethane Coatings

DIRECTIONS FOR USE

Rust Bullet Rapid Fire will reduce the cure time of Rust Bullet Coatings by approximately 80%. When added to a Rust Bullet Coating, Rapid Fire Accelerator will reduce the pot life to approximately 3 hours. Any product remaining after the 6 hour pot life should be discarded. Some slight variation in finish, such as gloss and color, may occur in Rust Bullet Coatings when the accelerator is used.

- **Add (1) Quart can (32 oz.) to each 5 Gallon Pail of Rust Bullet Coating**
- **Add (1) 6.4 oz. can to each 1 Gallon Can of Rust Bullet Coating**

Thoroughly stir the Rust Bullet Coating until completely homogenous (approximately 3 minutes) before adding Rust Bullet Rapid Fire Accelerator to the coating. Once the coating has been stirred, add the pre-measured amount of Rapid Fire Accelerator to the coating and stir only enough to incorporate the accelerator into the coating. Do not over stir.

Rust Bullet Rapid Fire Accelerator is designed for spray applications. Brush and roll applications are possible; however, the pot life will be reduced considerably when the treated coating is exposed to repeated dipping of brushes and or rollers.

CAUTION: CORROSIVE

Vapor harmful. May affect the brain or nervous system causing dizziness, headache, or nausea. Causes nose, throat and lung irritation. Combustible liquid. Forms combustible mixtures with air at or above the flash point. Keep away from heat, sparks and flame. Vapor may cause flash fire. Do not smoke. Extinguish all flames and pilot lights, and turn off all stoves, heaters, electric motors and other sources of ignition during use and until all vapors are gone. Prevent build-up of vapors by opening all windows and doors to achieve cross ventilation. Use with adequate ventilation, and if necessary, use only respiratory protection authorized in the U.S. Federal OSHA Respiratory Protection Standard (29 CFR 1910.134), equivalent U.S. State standards, Canadian CSA Standard Z94.4-93, the European Standard EN149, or EU member states. Ensure eyewash/safety shower stations are available near areas where this product is used. **IMPORTANT:** Protective clothing, gloves, and eye protection are recommended when using Rust Bullet® Rapid Fire™. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use. Do not get in eyes, on skin or clothing. Wash thoroughly after handling. **KEEP OUT OF REACH OF CHILDREN.**

FIRST AID

In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention; for skin, wash thoroughly with soap and water. Get medical attention if irritation persists. If affected by inhalation of vapor or spray mist, remove to fresh air. If necessary, restore breathing and get medical attention immediately. If swallowed, do not induce vomiting. Get medical attention immediately. Remove contaminated clothing and shoes. Thoroughly clean or destroy contaminated clothing or shoes before reuse. Keep container closed when not in use. If spilled, prevent bodily contact. Contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations. For more complete coverage of safety issues refer to the GHS SDS at www.RustBullet.com.

Information contained herein is, to our best knowledge, true and accurate, but all recommendations or suggestions are made without guarantee. Since the conditions of use are beyond our control, Rust Bullet, LLC (the Company), disclaims any liability incurred in connection with the use of our products and information contained herein. No person is authorized or empowered to make any statement or recommendation not contained herein, any such statement or recommendation so made shall not bind the Company. Furthermore, nothing contained herein shall be construed as a recommendation to use any product in conflict with existing patents covering any material or its use. The information is furnished upon the condition that the recipient shall make their own determination concerning suitability for their particular application.