



Rust Bullet® Solvent

SAFETY DATA SHEET

This document is prepared to the Globally Harmonized System of Classification and Labelling of Chemicals Guidelines 29CFR 1910 (OSHA HCS)

1. PRODUCT IDENTIFICATION

TRADE NAME (AS LABELED): Rust Bullet® Solvent
SYNONYMS: Solvent
CHEMICAL SHIPPING NAME/CLASS: Non-Hazardous for less than Bulk Shipment via Road or Rail within U.S. Petroleum Distillates, n.o.s., Class 3, PGIII
DOT Marine Pollutants: This product does not contain marine pollutants as defined in 49CFR171.8.
U.N. NUMBER: UN1268
MANUFACTURER'S NAME: Rust Bullet® LLC
ADDRESS: 300 Brinkby Avenue; Suite 200
 Reno, NV 89509
EMERGENCY PHONE: 800-424-9300 or 202-483-7616 (CHEMTREC, CCN17521)
BUSINESS PHONE: 775-829-5606 (For product information)
DATE OF CURRENT REVISION: December 19, 2022
DATE OF LAST REVISION: July 14, 2015

2. HAZARD IDENTIFICATION

GHS CLASSIFICATION:

Carcinogen Category 1B
 Flammable Liquid Category 3
 Aspiration Hazard Category 1

Acute Inhalation Toxicity category 4
 Eye Irritant Category 2

Skin Irritant Category 2
 STOT SE Category 3

Chronic Aquatic Toxicity Category 2

LABEL ELEMENTS

SIGNAL WORD: Danger




HMIS RATING SYSTEM

HAZARDOUS MATERIAL IDENTIFICATION SYSTEM			
HEALTH HAZARD (BLUE)		2	
FLAMMABILITY HAZARD (RED)		2	
REACTIVITY (YELLOW)		0	
PROTECTIVE EQUIPMENT			
EYES	RESPIRATORY	HANDS	BODY
	SEE SECTION 8		SEE SECTION 8

For Routine Industrial Use and Handling Applications

FLAMMABILITY



OTHER

Scale: 0 = Minimal 1 = Slight 2 = Moderate
 3 = Serious 4 = Severe * = Chronic hazard

Supplier Identification:

Rust Bullet® LLC
 300 Brinkby Avenue; Suite 200
 Reno NV 89509
 Phone: 775-829-5606



Rust Bullet® Solvent

SAFETY DATA SHEET

HAZARD STATEMENT:

- H226 Flammable Liquid and Vapor
- H304 May be fatal if swallowed and enters airways
- H332 Harmful if inhaled
- H350 May cause cancer
- H319 Causes serious eye irritation
- H335 May cause respiratory irritation
- H315 Causes skin irritation
- H312 Harmful in contact with skin
- H411 Toxic to aquatic life with long lasting effects

PREVENTION STATEMENT:

- P210 Keep away from heat/sparks/open flame/hot surfaces – No Smoking.
- P242 Use only non-sparking tools.
- P243 Take precautionary measures against static discharge.
- P261 Avoid breathing dust/fume/gas/mist/vapors/spray.
- P271 Use only in well ventilated areas.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.

RESPONSE STATEMENT:

- P363 Wash contaminated clothing before reuse.
- P301+P310 IF SWALLOWED: Immediately call a POISON CENTER or Doctor/Physician.
- P333 + P313 IF skin irritation or rash occurs: Get medical advice/attention.

HEALTH EFFECTS OR RISKS FROM EXPOSURE:

ACUTE:

INHALATION: Breathing of vapor or mist is possible. Breathing small amounts of this material during normal handling is not likely to cause harmful effects. Breathing large amounts may be harmful.

INGESTION: Swallowing small amounts of this material during normal handling is not likely to cause harmful effects. Swallowing large amounts may be harmful. This material can get into the lungs during swallowing or vomiting. This results in lung inflammation and other lung injury.

SKIN CONTACT: May cause mild skin irritation. Symptoms may include redness and burning of skin. Prolonged or repeated contact may dry the skin. Symptoms may include redness, burning, and drying and cracking of skin, skin burns, and other skin damage.

EYE CONTACT: May cause mild eye irritation. Symptoms include stinging, tearing, and redness.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE: Pre-existing disorders of the following organs (or organ systems) may be aggravated by exposure to this material: Skin, lung (for example, asthma-like conditions), Liver, Kidney, blood-forming system, immune system, auditory system, eye, Individuals with preexisting heart disorders maybe more susceptible to arrhythmias (irregular heartbeats) if exposed to high concentrations of this material.

CHRONIC:

This product does contain an ingredient(s) designated by IARC, NTP, ACGIH, OSHA or European Chemical Commission as probable or suspected human carcinogens.

3. COMPOSITION AND INFORMATION ON INGREDIENTS

Hazardous Ingredients:	WT%	CAS#	EINECS #	Hazard Classification	Risk Phrases EU
Solvent Naphtha (petroleum), Light Aromatic	40 – 50%	64742-95-6	265-199-0	Carc. Cat 2, Muta. Cat 2 [Xn] Harmful	R45, R46, R65
Trimethylbenzene, 1,2,4-	30 – 40%	95-63-6	202-436-9	[F] Flammable, [Xn] Harmful, [Xi] Irritant, [N] Dangerous to the Environment	R10, R20, R36/37/38, R51-53



Rust Bullet® Solvent

SAFETY DATA SHEET

Trimethylbenzene, 1,3,5-	5 – 10%	108-67-8	203-604-4	[F] Flammable, [Xi] Irritant, [N] Dangerous to the Environment	R10, R37, R51-53
Xylene	1.5 – 5%	1330-20-7	215-535-7	[F] Flammable, [Xi] Irritant	R10, R38
Cumene	1.5 – 5%	98-82-8	202-704-5	[F] Flammable, [Xn] Harmful, [Xi] Irritant, [N] Dangerous to the Environment	R10, R65, R37, R51-53
Diethylbenzene	1.5 – 5%	25340-17-4	246-874-9	None	None
Balance of other ingredients is less than 1% in concentration (or 0.1% for carcinogens, reproductive toxins, or respiratory sensitizers).					

NOTE: ALL WHMIS required information is included in appropriate sections based on the ANSI Z400.1-2010 format. This product has been classified in accordance with the hazard criteria of the CPR and the MSDS contains all the information required by the CPR, EU Directives and the Japanese Industrial Standard JIS Z 7250: 2000.

4. FIRST-AID MEASURES

SKIN EXPOSURE: If this product contaminates the skin, begin decontamination with running water. Remove exposed or contaminated clothing, taking care not to contaminate eyes. The contaminated individual should seek medical attention if any adverse effect occurs.

EYE EXPOSURE: If this product enter the eyes, open contaminated individual's eyes while under gently running water. Use sufficient force to open eyelids. Remove contact lenses if worn. Have contaminated individual "roll" eyes. Minimum flushing is for 15 minutes. Contaminated individual must seek medical attention if irritation develops or persists or if visual changes occur.

INHALATION: If vapors/mists generated by this product are inhaled, remove contaminated individual to fresh air. If necessary, use artificial respiration to support vital functions. **SEEK IMMEDIATE MEDICAL ATTENTION.**

INGESTION: If this product is swallowed, **CALL PHYSICIAN OR POISON CONTROL CENTER FOR MOST CURRENT INFORMATION.** DO NOT induce vomiting; if vomiting occurs spontaneously, keep head below hips to prevent aspiration of liquid into lungs. Never induce vomiting or give diluents (milk or water) to someone who is unconscious, having convulsions, or unable to swallow. **SEEK IMMEDIATE MEDICAL ATTENTION.**

RECOMMENDATIONS TO PHYSICIANS: Treat symptoms and eliminate overexposure.

5. FIRE-FIGHTING MEASURES

FLASH POINT: 100.2 °F / 37.9 °C Tag closed cup

AUTOIGNITION TEMPERATURE: 910 °F / 488 °C

FLAMMABLE LIMITS (in air by volume, %): Lower 1% Upper 7%

FIRE EXTINGUISHING MATERIALS: Use fire extinguishing methods listed below:

Water Spray: Yes

Carbon Dioxide: Yes

Foam: Yes

Dry Chemical: Yes

Halon: Yes

Other: Any "C" Class

UNUSUAL FIRE AND EXPLOSION HAZARDS: If product is heated above its flash point it will produce vapors sufficient to support combustion. Vapors are heavier than air and may travel along the ground and be ignited by heat, pilot lights, other flames and ignition sources at locations near the point of release.

Explosion Sensitivity to Mechanical Impact: No Information Available

Explosion Sensitivity to Static Discharge: Sensitive

SPECIAL FIRE-FIGHTING PROCEDURES: Incipient fire responders should wear eye protection. Structural firefighters must wear Self-Contained Breathing Apparatus and full protective equipment. Isolate materials not yet involved in the fire and protect personnel. Move containers from fire area if this can be done without risk; otherwise, cool with carefully applied water spray. If possible, prevent runoff water from entering storm drains, bodies of water, or other environmentally sensitive areas.



Rust Bullet® Solvent

SAFETY DATA SHEET

6. ACCIDENTAL RELEASE MEASURES

SPILL AND LEAK RESPONSE: Evacuate unprotected personnel from the area. Maintain adequate ventilation. Follow personal protective equipment recommendations found in section 8. Contain and recover liquid if possible. Use non-sparking tools and equipment. Collect liquid in an appropriate container or absorb with an inert material (e. g., vermiculite, dry sand, earth), and place in a chemical waste container. Do not use combustible materials, such as saw dust. Do not discharge to sewers and surface waters. Notify authorities if entry occurs. Remove all sources of ignition. U.S. Regulations (CERCLA) requires reporting spills and releases to soil, water and air in excess of reportable quantities. The toll free number for the US Coast Guard National Response Center is (800) 424-8802. Dispose of in accordance with U.S. Federal, State, and local hazardous waste disposal regulations and those of Canada and its Provinces, those of Australia, Japan and EU Member States (see Section 13, Disposal Considerations).

7. HANDLING and STORAGE

WORK PRACTICES AND HYGIENE PRACTICES: As with all chemicals, avoid getting this product ON YOU or IN YOU. Wash thoroughly after handling this product. Do not eat, drink, smoke, or apply cosmetics while handling this product. Do not breathe gas/fumes/ vapor/spray. Wear suitable protective clothing. In case of insufficient ventilation, wear suitable respiratory equipment. If ingested, seek medical advice immediately and show the container or the label.

STORAGE AND HANDLING PRACTICES: Containers of this material may be hazardous when emptied. Since emptied containers retain product residues (vapor, liquid, and/or solid), all hazard precautions given in the data sheet must be observed. Static ignition hazard can result from handling and use. Electrically bond and ground all containers, personnel and equipment before transfer or use of material. Special precautions may be necessary to dissipate static electricity for non-conductive containers. Use proper bonding and grounding during product transfer as described in National Fire Protection Association document NFPA 77. Warning! Sudden release of hot organic chemical vapors or mists from process equipment operating at elevated temperature and pressure, or sudden ingress of air into vacuum equipment, may result in ignitions without the presence of obvious ignition sources. Published "autoignition" or "ignition" temperature values cannot be treated as safe operating temperatures in chemical processes without analysis of the actual process conditions. Any use of this product in elevated temperature processes should be thoroughly evaluated to establish and maintain safe operating conditions.

Store in a cool, dry, ventilated area. Store out of direct sunlight.

8. EXPOSURE CONTROLS - PERSONAL PROTECTION

Chemical Name	CAS#	ACGIH TLV	OSHA TWA
Solvent Naphtha (petroleum), Light Aromatic	64742-95-6	Not Established	Not Established
Trimethylbenzene, 1,2,4-	95-63-6	25 ppm	25 ppm
Trimethylbenzene, 1,3,5-	108-67-8	25 ppm	25 ppm
Xylene	1330-20-7	100 ppm	100 ppm
Cumene	98-82-8	50 ppm	50 ppm
Diethylbenzene	25340-17-4	5 ppm	5 ppm

VENTILATION AND ENGINEERING CONTROLS: Use with adequate ventilation to ensure exposure levels are maintained below the limits provided below. Ensure eyewash/safety shower stations are available near areas where this product is used. *The following information on appropriate Personal Protective Equipment is provided to assist employers in complying with OSHA regulations found in 29 CFR Subpart I (beginning at 1910.132) or equivalent standard of Canada, or standards of EU member states (including EN 149 for respiratory PPE, and EN 166 for face/eye protection), and those of Japan. Please reference applicable regulations and standards for relevant details.*

RESPIRATORY PROTECTION: Maintain airborne contaminant concentrations below guidelines listed above, if applicable. If necessary, use only respiratory protection authorized in the U.S. Federal OSHA Respiratory Protection Standard (29 CFR 1910.134), equivalent U.S. State standards, Canadian CSA Standard Z94.4-93, the European Standard EN149, or EU member states.

EYE PROTECTION: Use chemical safety goggles and/or a full face shield where splashing is possible. Maintain eye wash fountain and quick-drench facilities in work area. Contact lenses pose a special hazard; Do not wear contact lenses.



Rust Bullet® Solvent

SAFETY DATA SHEET

If necessary, refer to U.S. OSHA 29 CFR 1910.133, Canadian Standards, and the European Standard EN166, Australian Standards, or relevant Japanese Standards.

HAND PROTECTION: Use chemically-resistant gloves when handling this product. If necessary, refer to U.S. OSHA 29 CFR 1910.138, the European Standard DIN EN 374, the appropriate Standards of Canada, Australian Standards, or relevant Japanese Standards.

BODY PROTECTION: Use body protection appropriate for task (e.g. lab coat, overalls). If necessary, refer to appropriate Standards of Canada, or appropriate Standards of the EU, Australian Standards, or relevant Japanese Standards. If a hazard of injury to the feet exists due to falling objects, rolling objects, where objects may pierce the soles of the feet or where employee's feet may be exposed to electrical hazards, use foot protection, as described in U.S. OSHA 29 CFR 1910.136.

9. PHYSICAL and CHEMICAL PROPERTIES

VAPOR DENSITY: 4.5

% VOLATILE: 100%

SOLUBILITY IN WATER: negligible

VAPOR PRESSURE: 2.100 mmHg @ 68.00 °F / 20.00 °C

ODOR: Characteristic

APPEARANCE and COLOR: Clear, colorless liquid with aromatic odor

EVAPORATION RATE (n-BuAc=1): slower than 1

MELTING/FREEZING POINT: -64 °F / -53 °C

BOILING POINT: (+/- 15)321 °F / 161 °C

pH: No Data

SPECIFIC GRAVITY: No Data

10. STABILITY and REACTIVITY

STABILITY: Stable under conditions of normal storage and use.

HAZARDOUS DECOMPOSITION PRODUCTS: carbon dioxide and carbon monoxide, Hydrocarbons, nitrogen oxides (NO_x), Sulphur oxides

MATERIALS WITH WHICH SUBSTANCE IS INCOMPATIBLE: alkalis, Nitric acid, Oxidizing agents, Strong acids, sulphuric acid

POSSIBILITY OF HAZARDOUS REACTIONS: Will not occur.

CONDITIONS TO AVOID: Heat, flames and sparks

11. TOXICOLOGICAL INFORMATION

TOXICITY DATA:

Acute oral toxicity : LD 50 Rat : > 5,600 mg/kg

Acute inhalation toxicity : LC 50 Rat: (>) 10,200 mg/m³; 4 hr

Acute dermal toxicity : LD 50 Rabbit: (>) 4,000 mg/kg

CARCINOGENICITY:

This product does contain an ingredient(s) designated by IARC, NTP, ACGIH, OSHA or European Chemical Commission as probable or suspected human carcinogens.

REPRODUCTIVE EFFECTS: No information found

MUTAGENICITY: No information found

NEUROTOXICITY: No information found

12. ECOLOGICAL INFORMATION

ALL WORK PRACTICES MUST BE AIMED AT ELIMINATING ENVIRONMENTAL CONTAMINATION.

ENVIRONMENTAL STABILITY: When released into the soil, this material may leach into groundwater. When released into water, this material may biodegrade to a slight extent. This material is expected to significantly bioaccumulate.

CHEMICAL EFFECT ON PLANTS, ANIMALS AND AQUATIC LIFE:

Toxicity to fish

SOLVENT NAPHTHA (PETROLEUM), LIGHT

AROMATIC: no data available

TRIMETHYLBENZENE 1,2,4- : 96 h flow-through test LC 50 Fathead minnow (Pimephales promelas): 7.19 - 8.28 mg/l ; Mortality

TRIMETHYLBENZENE, 1,3,5- : 96 h flow-through test LC 50 Goldfish (Carassius auratus): 9.89 - 15.05 mg/l



Rust Bullet® Solvent

SAFETY DATA SHEET

XYLENE : 96 h static test LC 50 Fathead minnow (Pimephales promelas): 23.53 - 29.97 mg/l

CUMENE : 96 h LC 50 Rainbow trout, donaldson trout

(Oncorhynchus mykiss): 2.70 mg/l Method: Renewal; Mortality

DIETHYLBENZENE : no data available

Toxicity to daphnia and other aquatic invertebrates.

SOLVENT NAPHTHA (PETROLEUM), LIGHTAROMATIC: no data available

TRIMETHYLBENZENE 1,2,4- : no data available

TRIMETHYLBENZENE, 1,3,5- : 24 h static test EC 50 Water flea (Daphnia magna): 50.00 mg/l

XYLENE : 24 h static test LC 50 Water flea (Daphnia magna): >100.00 - < 1,000.00 mg/l

CUMENE : 48 h EC 50 Water flea (Daphnia magna): 7.90 - 14.10mg/l Method: Static Intoxication

DIETHYLBENZENE : no data available

13. DISPOSAL CONSIDERATIONS

PREPARING WASTES FOR DISPOSAL: Waste disposal must be in accordance with appropriate U.S. Federal, State, and local regulations, those of Canada, Australia, EU Member States and Japan.

14. TRANSPORTATION INFORMATION

US DOT, IATA, IMO, ADR:

U.S. DEPARTMENT OF TRANSPORTATION (DOT) SHIPPING REGULATIONS: This product is classified (per 49 CFR 172.101) by the U.S. Department of Transportation, as follows.

Domestic (Land, D.O.T.) – When shipped in less than a 119 gallon container

PRODUCT LABEL: Rust Bullet® Solvent
UN NUMBER: None
D.O.T. HAZARD CLASS: None
PACKING GROUP: None
D.O.T. SHIPPING NAME: Non-Regulated Material
SPECIAL PROVISIONS: None

International (Water, I.M.O.):

PRODUCT LABEL: Rust Bullet® Solvent
UN NUMBER: UN 1268
D.O.T. HAZARD CLASS: Class 3, Flammable
PACKING GROUP: PG III
D.O.T. SHIPPING NAME: Petroleum Distillates,
n.o.s. PRODUCT RQ (Lbs): N.A.
EMS: F-E, S-E

International (Air, I.C.A.O.):

PRODUCT LABEL: Rust Bullet® Solvent
UN NUMBER: UN 1268
D.O.T. HAZARD CLASS: Class 3, Flammable
PACKING GROUP: PG III
D.O.T. SHIPPING NAME: Petroleum Distillates, n.o.s.

AIR-CARGO: Packing Instructions: 366 Maximum Quantity: 220L

AIR-PASS.: Packing Instructions: 355 Maximum Quantity: 60L

Special Instructions: --

MARINE POLLUTANT: The components of this product are not designated by the Department of Transportation to be Marine Pollutants (49 CFR 172.101, Appendix B).

INTERNATIONAL AIR TRANSPORT ASSOCIATION SHIPPING INFORMATION (IATA): This product is considered as dangerous goods.

INTERNATIONAL MARITIME ORGANIZATION SHIPPING INFORMATION (IMO): This product is considered as dangerous goods.

EUROPEAN AGREEMENT CONCERNING THE INTERNATIONAL CARRIAGE OF DANGEROUS GOODS BY ROAD (ADR): This product is considered by the United Nations Economic Commission for Europe to be dangerous goods.



SAFETY DATA SHEET

15. REGULATORY INFORMATION

UNITED STATES REGULATIONS:

U.S. SARA REPORTING REQUIREMENTS: The components of this product are subject to the reporting requirements of Sections 302, 304, and 313 of Title III of the Superfund Amendments and Reauthorization Act.

SARA 313: TRIMETHYLBENZENE 1,2,4- CAS# 95-63-6 36.00 %, XYLENE CAS# 1330-20-7 3.00 %, CUMENE CAS# 98-82-8 3.00 %

U.S. SARA THRESHOLD PLANNING QUANTITY: There are no specific Threshold Planning Quantities for the components of this product. The default Federal MSDS submission and inventory requirement filing threshold of 10,000 lbs (4,540 kg) therefore applies, per 40 CFR 370.20.

U.S. CERCLA REPORTABLE QUANTITY (RQ): XYLENE 1330-20-7 100 lbs

U.S. TSCA INVENTORY STATUS: The components of this product are listed on the TSCA Inventory or are exempted from listing.

STATE REGULATIONS:

CALIFORNIA SAFE DRINKING WATER AND TOXIC ENFORCEMENT ACT (PROPOSITION 65): Ingredient(s) within this product are on the Proposition 65 Lists.

WARNING! This product contains a chemical known to the State of California to cause cancer.	Cumene Benzene
WARNING! This product contains a chemical known to the State of California to cause birth defect or other reproductive harm.	Benzene

CANADIAN REGULATIONS:

CANADIAN DSL/NDL INVENTORY STATUS: The components of this product are on the DSL Inventory, or are exempted from listing.

OTHER CANADIAN REGULATIONS: Not applicable.

CANADIAN ENVIRONMENTAL PROTECTION ACT (CEPA) PRIORITIES SUBSTANCES LISTS:

WHMIS: This SDS has been prepared according to the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all of the information required by the CPR.

CANADIAN WHMIS CLASSIFICATION and SYMBOLS: CLASS B-3: Flammable liquid with a flash below 37.8°C, CLASS D-2B: Material causing other toxic effects.



EUROPEAN ECONOMIC COMMUNITY INFORMATION:

EU LABELING AND CLASSIFICATION: This product meets the definition of the following hazard class as defined by the European Economic Community Guidelines.

EU CLASSIFICATION: [F] Flammable, [Xn] Harmful, [Xi] Irritant, [N] Dangerous to the Environment

EMERGENCY OVERVIEW: Danger!

Product Description: This product is a clear, colorless liquid with an aromatic odor.

Health Hazards: Warning! May affect the central nervous system causing dizziness, headache or nausea. Prolonged or repeated contact may dry the skin and cause irritation and burns.

Flammability Hazards: Flammable Liquid and Vapor.

Reactivity Hazards: This product is not reactive.

Environmental Hazards: Release of the product is expected to cause adverse effects to the aquatic environment.

Emergency Recommendations: Emergency responders must have personal protective equipment and fire protection appropriate for the situation to which they are responding.



Rust Bullet® Solvent

SAFETY DATA SHEET

EU LABELING AND CLASSIFICATION: This product meets the definition of a hazardous substance or preparation according to EU Regulations (EC) No 1272/2008.

INDEX NUMBER:

EC# 265-199-0 Annex1 Index# 649-356-00-4

EC# 202-436-9 Annex 1 Index# 601-043-00-3

EC# 203-604-4 Annex 1 Index# 601-025-00-5

EC# 215-535-7 Annex 1 Index# 601-022-00-9

EC# 202-704-5 Annex 1 Index# 601-024-00-X

EC# 246-874-9 This substance is not classified in the Annex I of Directive 67/548/EEC

EU RISK PHRASES: R10: Flammable; R65: Harmful may cause lung damage if swallowed, R37; Irritating to the respiratory system, R51/53: Toxic to aquatic organisms, may cause long term adverse effects in the aquatic environment.

EU SAFETY PHRASES: S9: Keep container in well ventilated space; S24/25: Avoid contact with skin and eyes; S51: Use only in a well ventilated area; S61: Avoid release to the environment; S62: If swallowed, do not induce vomiting; seek immediate medical advice.

AUSTRALIAN INFORMATION FOR PRODUCT: The components of this product are listed on the International Chemical Inventory list.

JAPANESE INFORMATION FOR PRODUCT:

JAPANESE MINISTER OF INTERNATIONAL TRADE AND INDUSTRY (MITI) STATUS: The components of this product are not listed as Class I Specified Chemical Substances, Class II Specified Chemical Substances, or Designated Chemical Substances by the Japanese MITI.

JAPANESE ENCS INVENTORY: The components of this product are on the ENCS Inventory as indicated in the section on International Chemical Inventories.

POISONOUS AND DELETERIOUS SUBSTANCES CONTROL LAW: No component of this product is a listed Specified Poisonous Substance under the Poisonous and Deleterious Substances Control Law.

INTERNATIONAL CHEMICAL INVENTORIES:

Listing of the components on individual country Chemical Inventories is as follows:

Asia-Pac: Listed

Australian Inventory of Chemical Substances (AICS): Listed

Korean Existing Chemicals List (ECL): Listed

Japanese Existing National Inventory of Chemical Substances (ENCS): Listed

Philippines Inventory of Chemicals and Chemical Substances (PICCS): Listed

Swiss Giftlist List of Toxic Substances: Listed

U.S. TSCA: Listed

16. OTHER INFORMATION

Prepared By: V.C. Bud Jenkins BS, MBA, JD, Certified Hazardous Materials Manager, Certified Hazardous Waste Practitioner.

Date: December 19, 2022

This information is furnished gratuitously and independent of the sales of the product without warranty, expressed or implied, except that it is accurate to the best knowledge of Rust Bullet®. NO WARRANTY, EITHER EXPRESS OR IMPLIED, WHETHER OF MERCHANTABILITY OF FITNESS OF ANY NATURE OR OTHERWISE WITH RESPECT TO THE PRODUCT OR TO THE DATA HEREIN IS MADE HEREUNDER. The data on this sheet are related only to the specific material designated herein. Rust Bullet assumes no legal responsibility for use or reliance upon these data. Rust Bullet shall not be responsible for any damages directly or indirectly resulting from the publication or use of or reliance upon data contained herein. Safety Data Sheets are available for all Rust Bullet products and you are urged to obtain those sheets for all those products that you buy, process, use or distribute. You may also have a legal obligation to advise anyone working with or exposed to such products of the information contained in the Safety Data Sheets.

END OF SDS